

Super Universal Tractor Oil. Part N^o. A-609

Product Description:

This product is a super universal tractor oil grade suitable for engines, transmissions, hydraulics and final drives.

The latest agricultural machinery in today's intensive farming environment needs the protections of a high quality lubricant.

This product is blended from carefully selected base oils and the latest in additive technology to produce a lubricant for the demands of most farm equipment. The latest additives used help reduce wet brake noise. The carefully selected base oils ensure protection even under the most arduous of conditions.

Benefits:

- Meets the majority of OEM requirements
- Helps reduce wet brake noise
- Suitable for most agricultural machinery requirements
- High API diesel specification

Application:

The product is suitable for use in both normally aspirated and turbo charged diesel and petrol engines, transmission systems including those fitted with wet brakes, hydraulic systems, oil immersed clutches, gearboxes and final drives. It is suitable for agricultural, plant and off road machinery.

Product Specification:

API	CE/SF (engine) GL-4 (gears)
CCMC	D4/G2
MB	227.1
Massey Ferguson	1135, 1137, 1139
Ford	M2C 86A, 121B, 134B/C, 159B
Case	1206, 1207
Allison	C4
John Deere	J20A, J27
ZF	TE ML 05, 06, 07
Caterpillar	TO-2

Typical Test Data:

Grade	15W40
SG @ 15.6 °C	0.883
KV @ 100 °C (cSt)	11.49
KV @ 40 °C (cSt)	85.04
VI	125
Flash Point COC (°C)	218
Pour Point °C	-29
TBN (mg KOH/g)	10.38

Health & Safety (Group 1):

Please Refer to corresponding Health & Safety Data Sheet

Availability:

This product is available in 25 litre drums